

Thermally separated ceiling connector

Reinforced concrete slab with superstructure, cantilevered Monolithic masonry Detailed view above door | under window with blinds

DCIK 07-04-TFJ | M 1 : 10



	component, example		Component, example
1	Exterior plaster	10	Reinforced concrete ceiling
2	Blinds, thermally insulated box	1	Threshold, thermally insulated
3	Interior plaster	12	Plastering profile or elastic connector
4	Insulation	13	Slab in gravel bed
5	Thermal insulation, non-slip (XPS)	(14)	Window element, door element
6	Reinforced concrete slab	15	Facade channel
\bigcirc	Schöck Isokorb® XT type K	16	Sloping wedge (e.g., bonded screed)
8	Floor covering, floating screed	1	Drain mat with fleece
9	Impact sound and thermal insulation	(18)	Edge finish: Channel, gravel trap, inlet plate

Note: This detailed view is a general, non-binding planning proposal which only provides a schematic overview of the construction work. The planner and processor are responsible for checking applicability and completeness for each construction project. Adjacent components are only shown schematically. All specifications and assumptions must be adapted or coordinated to local conditions. The respective technical specifications of the data sheets, processing guidelines, standards, and system approvals must be observed. Balconies, arcades, and canopies require their own statics.