


Thermally separated ceiling connector

Prefabricated reinforced concrete balcony, upward height offset

Wall with rear-ventilated facade (RVF)

Detailed view above wall | below wall

DCIK 17-01-WW | M 1 : 10



Component, example	
①	Rear-ventilated facade (RVF)
②	Masonry wall or reinforced concrete wall
③	Interior plaster
④	Insulation
⑤	Thermal insulation, mineral wool
⑥	Precast reinforced concrete, waterproof concrete
⑦	Schöck Isokorb® XT type K-O
⑧	Floor covering, floating screed
⑨	Impact sound and thermal insulation

Component, example	
⑩	Reinforced concrete ceiling
⑪	Base insulation, XPS
⑫	Rear ventilation
⑬	Railing
⑭	Reinforced concrete overlay, based on statics
⑮	Schöck Isolink® type F-S1
⑯	Insulation holder

Note: This detailed view is a general, non-binding planning proposal which only provides a schematic overview of the construction work. The planner and processor are responsible for checking applicability and completeness for each construction project. Adjacent components are only shown schematically. All specifications and assumptions must be adapted or coordinated to local conditions. The respective technical specifications of the data sheets, processing guidelines, standards, and system approvals must be observed. Balconies, arcades, and canopies require their own statics.