


Thermally separated ceiling connector

Steel balcony, cantilevered

Double-wall masonry

Detailed view above door | under window with blinds

DCIK 27-04-TFJ | M 1 : 10



Component, example	
①	Exposed brickwork, clinker
②	Reinforced concrete lintel
③	Interior plaster
④	Blinds, thermally insulated box
⑤	Aluminum composite panel, substructure
⑥	Steel profiles with corrosion protection
⑦	Schöck Isokorb® XT type SK
⑧	Floor covering, floating screed
⑨	Impact sound and thermal insulation

Component, example	
⑩	Reinforced concrete ceiling
⑪	Threshold, thermally insulated
⑫	Elastic joint
⑬	Railing
⑭	Window element, door element
⑮	Facade channel
⑯	Wooden floorboards, substructure, support system
⑰	Sloped aluminum tray
⑱	Head plate with cleat, optional adapter

Note: This detailed view is a general, non-binding planning proposal which only provides a schematic overview of the construction work. The planner and processor are responsible for checking applicability and completeness for each construction project. Adjacent components are only shown schematically. All specifications and assumptions must be adapted or coordinated to local conditions. The respective technical specifications of the data sheets, processing guidelines, standards, and system approvals must be observed. Balconies, arcades, and canopies require their own statics.