

Certificate

Certified Passive House Component

for cool, temperate climate, valid until 31.12.2024

Category: Balcony connection

Slab thickness 160 - 250 mm

Manufacturer: Schöck Bauteile GmbH

76534 Baden-Baden, GERMANY

Product name: Schöck Isokorb® CXT Typ K

The following criteria were used in awarding this certificate:

Efficiency Criterion

In two typical applications*, the construction fulfills the requirement of

 $\Delta U_{WB} \leq 0.010 \text{ W/(m}^2\text{K)}$

Comfort Criterion

The inner surface must be warm enough to prevent mould as well as uncomfortable down-drought and radiation losses.

θ_{i,min} ≥ 17°C

Following heat transmission coefficients ψ [W/(mK)] have been validated:

Product	slab thickness [mm]			
	180	200	220	250
CXT Typ K-M1V1	-	0.074	-	-
CXT Typ K-M1V2	-	0.080	-	-
CXT Typ K-M2V1	-	0.078	-	-
CXT Typ K-M2V2	-	0.084	-	-
CXT Typ K-M3V1	0.082	0.085	-	0.093
CXT Typ K-M3V2	0.091	0.094	-	0.103
CXT Typ K-M4V1	-	0.090	-	-
CXT Typ K-M4V2	-	0.098	ı	-
CXT Typ K-M5V1	-	0.098	-	-
CXT Typ K-M6V1	-	0.104	-	-

* The criterion was validated on both, a row house and a apartment dwelling.

(according to criteria "balcony connection" v2.1.1)

The certificate includes types with minor statical performance. Thermal bridge coefficients can be approximated by linear interpolation.

www.passivehouse.com

Passive House Institute Dr. Wolfgang Feist 64283 Darmstadt GERMANY



